

Dayron® & Dayron® I

More safety through upgraded visibility!

With the Dayron®/Dayron® I a new innovative product is added to the Kellermann portfolio: For the first time a daytime running with position light or combined position light / indicator is introduced. In line with the Kellermann DNA to aim for more safety through maximum visibility the Dayron®/Dayron® I sets new benchmarks. Thanks to an outstanding newly introduced lens technology an exceptionally impressive brightness is achieved.** The Kellermann Dayron®/Dayron® I currently is the strongest daytime running light with ECE approval in the market worldwide!

Dayron® - style meets multi-function

The Kellermann Dayron®/Dayron® I can be installed on almost all motorcycles with or without daytime running light as standard.* With the Dayron® I Kellermann introduces the first daytime running light with an integrated indicator where the complete illumination surface is switching from white to yellow during the flashing process. Apart from its technical versatility the Dayron®/Dayron® I also impresses with an outstanding design: Embedded in an elegant flow-optimized aluminium casing it is the ultimate eyecatcher on every bike.

Electronic accessories will be available soon.

* Electrical accessories may be required to match indicators signal frequency.

** Combination out of the IC operated Longlife Protection Guard® system with high-performance-LEDs latest type of construction.

ECE-tested for front

- Increased safety because of improved visibility
- Replaces the existing daytime running light and position if applicable also the indicator
- Automatic switching of daytime running light to position light when the low beam is activated
- Automatic deactivation of daytime running light/position light during flashing
- Exceptionally brilliant lighting surface through newly introduced lens technology
- Extreme light power
- Kellermann HighPower LED Technology
- Longlife Protection Guard®, IC operated, 330 kHz
- Flow-optimized aluminium casing
- Suitable for 12 volt DC applications
- With M8 x 20 adapter
- Global design protection